



# SUPERIOR MULTIFLEET L.S. SAE 15W40

Multi-grade Diesel Engine Oil – For Severe Conditions

## Description

Superior Multifleet L.S. is a new generation, 'Low SAPS', extra high performance lubricant, formulated from specially selected, high-quality base oils and a customized additive package.

It supports the exceptional performance of modern heavy-duty engines and offers complete protection of the DPF.

This oil offers the following advantages:

- Full after-treatment system protection.
- Lower maintenance cost
- Total engine protection: outstanding engine cleanliness and durability.
- Long oil drain intervals.
- Life time of particulate filters

## Quality level

API	CJ-4, CI-4
ACEA	E7-04 Issue 2, E9-08
CATERPILLAR	ECF-2, ECF-3
CUMMINS	CES 20081
DDC	93K218
MB	228.31
MAN	M 3275
MTU	Type 2
VOLVO	Approval VDS-4
RENAULT TRUCKS	RLD-3
MACK	EO-O PP-07
GLOBAL	DHD-1
JASO	DH-1, 2

## Available in

Barrels of 30, 60 and 208 L.

## Application

Superior Multifleet L.S. is recommended for the latest 4-stroke diesel engines fitted with DPF, which have to answer to the strict limitations of exhaust gases.

Equally suitable for older diesel engines with EGR (Euro III, IV and V + Tier I, II, III and IV).

Exceeds the demanding requirements of most U.S., European and Japanese manufacturers.

## Photo



## Typical properties

	SAE 15W40
Density 15°C	0.871
Viscosity cst 40°C	100
Viscosity cst 100°C	13.8
Viscosity index	139
Pourpoint °C	-37
Flashpoint COC °C	228
Sulphated Ash	1.0

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)

TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.

URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)