



ANTI FREEZE LONG LIFE

Cooling System Protector

Description

Anti Freeze Long Life is an undiluted fluid, based on mono-ethylene-glycol with anti-corrosion additives. This fluid contains no phosphates, amines or nitrates and guarantees a complete and permanent protection of the cooling system. To be diluted with demineralized water. Protection temperature:

% ANTI FREEZE: FREEZING POINT:

30% - 18 ° C

40% - 28 ° C

50% - 40 ° C

Quality level

SAE: J1034
AFNOR: 15-601/191
ASTM: D3306, D4985
BS: 6580-1992

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 210 L.

Application

Intended for open and closed cooling circuits of vehicles and/of heatings.

Photo



Typical properties

Density at 20°C	1.128
Reserve alkalinity ml 0.1M HCl	21.1
Color	Blue
Water content % wt/wt	3.5

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. ● Kromstraat 54 ● 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. ● FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> ● EMAIL denicol@denicol.com