



---

# FORK FLUID 400

Extreme Competition

---

## Description

Fork Fluid 400 is an excellent fork oil with:

- Outstanding anti-wear characteristics. It extends equipment life and reduces maintenance and downtime.
- Strong oxidation and thermal stability.
- Reusable after water is removed because Fork Fluid 400 separates water readily without loss of performance additives.
- Extended oil change intervals.
- Very high viscosity index.
- Dyno and track tested
- For all aluminum and steel bodies
- SAE viscosity grade between SAE 3.5 to SAE 7.5 due to the very high viscosity index

## Available in

Carton of 24x1 L.  
Barrels of 30, 60 and 208 L.

## Application

For all aluminum and steel bodies.

## Photo



## Typical properties

Viscosity cst 40°C	13.4
Viscosity cst 100°C	5.16
Viscosity index	395
Pourpoint °C	-48
Flashpoint COC °C	145
Four ball wear test, scar diam. (mm) 1 hour @40 kg, 1200rpm @75°C/167°F	0.75

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)