



HYDRAULIC OIL

ISO 22 - ISO 32 - ISO46 - ISO68 - ISO100

Mineral Oil

Description

This mineral oil, specifically developed to come up to the expectations and requirements, concerning temperatures, speeds or high pressure, of the most important manufacturers of hydraulic equipment, contains anti-oxidant, anti-corrosion, anti-wear and anti-foam additives. Being recommended by Vickers, Gresen, HPM, Worthington, Gerotor, Vickers Hydreco and Cessna, it can also be used to lubricate screw compressors, workshop material, bearings, compressed air systems or reducing gears.

Quality Level

ISO	11158, HM / 6743-4, HM
DIN	51524 part 2
AFNOR	48-603 HM, NF E 48-690, NF E 48-691
DENISON	HF-2
EATON VICKERS	I-286-S, M-2950-S

Available in

Cartons of 24x1 L et 6x5 L.
Barrels of 30, 60 et 208 L.

Application

Lubrication of hydraulic systems.

Photo



Typical properties

	<u>ISO 22</u>	<u>ISO 32</u>	<u>ISO 46</u>	<u>ISO 68</u>	<u>ISO 100</u>
Density 15°C	0.865	0.872	0.880	0.885	0.887
Viscosity cst 40°C	21.3	31.4	46.6	69	101
Viscosity cst 100°C	4.4	5.4	7	8.7	11.4
Viscosity index	117	106	107	97	99
Pourpoint °C	-30	-30	-30	-30	-24
Flashpoint COC °C	195	207	220	230	232

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. ● Kromstraat 54 ● 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. ● FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> ● EMAIL denicol@denicol.com