



LITHIUM COMPLEX GREASE EP 2

High Performance and High Temperature Grease

Description

Lithium Complex Grease EP 2 is a modern highly qualified grease, with lithium complex as a thickener.

Due to the lithium complex soap, the antioxidants, the corrosion inhibitors and its EP/AW additives, this grease has the following capacities:

- Very high mechanical stability
- Outstanding anticorrosion protection
- Withstands high temperatures
- Prolongs the intervals of re-lubrication
- Suitable for applications within a wide temperature range
- Universal grease for both industrial and automotive industry

Quality level

NLGI 2

Available in

Carton of 24x400 Gr (Tubes)
Bottles of 1 and 5 Kg.
Barrels of 18, 50 and 180 Kg.

Application

Suitable for all types of bearings, including those who operate under heavy load conditions for both industrial and automotive industry.

Photo



Typical properties

Thickener	Lithium Complex
Dropping point	>260° C
Base oil viscosity cst 40°C	210
Base oil viscosity cst 100°C	18
4-Ball weld load	2800 N
Temperature range	-30°→140° C
Colour	Yellowish-Brown

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com