



---

## PRO ULTRA-FE SAE 5W30

Hi-Tech Synthetic Fuel Economy Engine Oil

---

### Description

Pro Ultra-Fe is a "Mid-SAPS" motor oil, developed to meet the Ford WSS-M2C-913C/D specifications, which combines a highly enhanced lubrication together with a lower fuel consumption.

Replaces the earlier M2C-913-A/B requirements.  
Full compatible with DPF's.

### Quality level

API SL-CF  
ACEA A1/B1-A5/B5  
FORD WSS-M2C-913C/D  
RENAULT RN 0700

### Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

### Application

Suitable for the Ford WSS-M2C-913C/D specifications and for the vehicles equipped with the 2,2 Duratorq TDCI engines.

### Photo



### Typical properties

	SAE 5W30
Density 15°C	0.860
Viscosity cst 40°C	55
Viscosity cst 100°C	9.95
Viscosity index	170
Pourpoint °C	-39
Flashpoint COC °C	230

Average oil analysis without engagement

**DENICOL**  
LUBRICANTS

DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)