



RACING COMPETITION BRAKE FLUID

High performance – 100 % Synthetic Brake Fluid

Description

Racing Competition Brake has been specially formulated for extreme racing conditions where braking systems must operate at very high temperatures.

- Very low pourpoint
- Does not affect seals
- Minimal corrosion

Quality level

SAE J-1703
 FMVSS exceeds 116 DOT 4
 Exceeds DOT 5.1 - DOT 3/4
 ISO 4925

Available in

Cartons of 18x500ml.

Application

To be used under extreme racing conditions where braking systems must operate at very high temperatures. Bleed the system before each race with this fluid to obtain the best results, certainly if the brakes are extremely hot and/or the conditions are humid. Do not mix "Racing Competition Brake Fluid" with other brake fluids in order not to compromise its outstanding performance

Photo



Typical properties

Kinematic Viscosity cst - 40°C	1750
Kinematic Viscosity cst 100°C	2.5
Ph	7-11.5
Dry Boiling Point (ERBP)°C	312
Wet Boiling point (WERBP)°C	205

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
 URL <http://www.denicol.com> • EMAIL denicol@denicol.com