



BIKER 4-STROKE SAE 10W40 – 15W40 – 15W50 – 20W50

High Performance – Multi-grade 4-Stroke Motorcycle Oil

Description

Biker 4-Stroke is a multi-grade engine oil, specially developed for use in four-stroke engines. The product is formulated from quality base oils with advanced synthetic additives. The special composition makes it possible to use this oil under the most varied conditions from idling to full acceleration. Tests have shown that the active components of the oil retain their optimum function even under the most unfavorable conditions. Can be used in summer as in winter.

Quality level

API: SG
JASO: MA

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

For road & race engines.

Photo



Typical properties

| | SAE 10W40 | SAE 15W40 | SAE 15W50 | SAE 20W50 |
|---------------------|-----------|-----------|-----------|-----------|
| Density 15°C | 0.876 | 0.880 | 0.876 | 0.893 |
| Viscosity cst 40°C | 91 | 103 | 134 | 155 |
| Viscosity cst 100°C | 14.1 | 13.9 | 17.6 | 18.0 |
| Viscosity index | 160 | 137 | 145 | 125 |
| Pourpoint °C | -40 | -33 | -36 | -28 |
| Flashpoint COC °C | 224 | 220 | 237 | 235 |

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com