



---

# BRAKE FLUID DOT 5.1

Synthetic Brake Fluid

---

## Description

Brake Fluid Dot 5.1 is a synthetic brake fluid having the following properties:

- A very low pour point
- A very good compatibility with seals and gaskets
- Restricting signs of corrosion
- High reflux- and wet boiling point
- Mixable with Dot 3 and Dot 4

## Quality level

SAE J-1703  
FMVSS 116 DOT 5.1

## Available in

Cartons of 24x250 MI, 24x1 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

Applicable for all hydraulic brake systems with drum or diskbrakes, requiring a synthetic SAE J 1703/DOT 5.1 brake fluid type.  
This brake fluid is extremely well applicable if high brake-system temperatures are to be considered and if very low temperatures in combination with ABS-systems are to be expected.

## Photo



## Typical properties

Density 20°C	1.069
Kinematic Viscosity cst - 40°C	810
Kinematic Viscosity cst 100°C	2.16
Ph	7.5
Reflux Boiling Point (ERBP)°C	275
Wet Boiling point (WERBP)°C	187

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)