



0

## HYPOID GEAR OIL L.S. SAE 80W90

Extreme pressure Limited slip Transmission oil

### Description

Hypoid Gear Oil L.S. is a unique mineral gear oil, composed of paraffinic base oils and selected additives, especially designed for the lubrication of the so called "Limited slip" and "Auto-locked" hypoid transmissions.

- Excellent frictional properties guarantees a smooth shift performance.
- A very good anti-wear protection assures a longer transmission life.
- Extended oil life: proves resistance to oil degradation.
- Excellent anti-wear, anticorrosion and anti-oxidation properties.

### Quality level

API: GL-5  
MIL: L-2105 B/C/D  
ZF: TE-ML 05C/12C

### Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

### Application

For the lubrication of the so called "Limited slip" and "Auto-locked" hypoid transmissions. Especially designed for the lubrication of the so called "Limited slip".

### Photo



### Typical properties

|                     |       |
|---------------------|-------|
| Density 15°C        | 0.897 |
| Viscosity cst 40°C  | 145   |
| Viscosity cst 100°C | 14.4  |
| Viscosity index     | 97    |
| Pourpoint °C        | -30   |
| Flashpoint COC °C   | 210   |

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)