



SYNTEX GRADE SAE 10W40 – 15W50

High Performance - Semi Synthetic Multi-grade Engine Oil

Description

Syntex Grade is a super multi-grade engine oil of the latest generation, especially designed for the lubrication of all 4-stroke gasoline and diesel engines.

- High fluidity at low temperature due to the use of synthetic components
- Fuel economy (EC=Energy Conserving)
- Easy to start in cold weather
- Stable viscosity at high temperature
- Very high resistance against ageing
- Low oil loss by evaporation

Quality level

API	SL/CF
ACEA	A3/B3/B4
VW	501.01/505.00 (1/97)
MB	229.1
BMW	SPECIAL OIL
PORSCHE	GL

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

For all 4-stroke gasoline and diesel engines, with or without turbo.

Photo



Typical properties

	SAE 10W40	SAE 15W50
Density 15°C	0.866	0.883
Viscosity cst 40°C	91	135
Viscosity cst 100°C	13.8	17.5
Viscosity index	155	143
Pourpoint °C	-39	-26
Flashpoint COC °C	220	230

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
 URL <http://www.denicol.com> • EMAIL denicol@denicol.com