



ULTRA SYNTRUCK SAE 10W40

Full Synthetic Performance Diesel Oil

Description

Ultra Syntruck SAE 10W40 is a full synthetic Ultra High Performance Diesel (UHPD) engine oil, meeting the highest performance standards for heavy duty trucks. It can be used for those engines which are equipped with particulate filters, in combination with low sulfur diesel fuel (max. 50 ppm).

Quality level

API	CI-4
ACEA	E6-08/E7-08
MB	228.5, 228.51
MAN	M 3277 (for CRT), M 3477
MTU	TYPE 3.1
VOLVO	VDS-3
DEUTZ	DQC-III-10LA
CUMMINS	CES 20076-20077
DAF	EXTENDED DRAIN
RENAULT	RGD-RXD-RL2
JASO	DH-2

Available in

Barrels of 30, 60 and 208 L.

Application

Ultra Syntruck SAE 10W40 is intended for truck fleet operators, seeking the best available lubricating oil technology, in order to meet the stringent emission limits, as requested by the Euro-4 and Euro-5 emission standards. This oil may also be used in previous generations of diesel engines (Euro 1, 2 and 3).

Photo



Typical properties

	SAE 10W40
Density 15°C	0.858
Viscosity cst 40°C	86.2
Viscosity cst 100°C	14.0
Viscosity index	168
Pourpoint °C	-39
Flashpoint COC °C	230
Sulphated Ash	1.0

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com