



# COMPRESSOR OIL ISO VG 32-46-68-100-150

Highly Refined Lubricant For Compressors

## Description

Compressor Oil is an excellent lubricant, specially designed from high quality base oils and its additives.

It is perfectly suitable for air compressors with high temperatures or where ever an oil is requested that meets the DIN class VDL.

This oil guarantees an exceptional protection against oxidation, foaming, corrosion or wear. It meets the very strict standards of the PNEUROP-oxidation test.

## Quality level

DIN 51506 VDL  
PNEUROP DIN 51.352

## Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

Specially designed from high quality base oils and its additives.

It is perfectly suitable for air compressors with high temperatures or where ever an oil is requested that meets the DIN class VDL.

## Photo



## Typical properties

	ISO 32	ISO 46	ISO 68	ISO 100	ISO 150
Density 15°C	0.873	0.881	0.880	0.891	0.891
Viscosity cst 40°C	32.5	45.7	66.6	96	145
Viscosity cst 100°C	5.4	6.8	8.7	10.9	14.5
Viscosity index	99	103	101	97	98
Pourpoint °C	-29	-23	-20	-19	-14
Flashpoint COC °C	218	237	254	276	295

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)

TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.

URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)