



---

## COOLING LIQUID AUTO

Aluminium and Magnesium Safe

---

### Description

Cooling Liquid Auto is an up-to-date 'long life' automotive coolant based on mono-ethylene glycol and softened water with addition of additives, to obtain the following properties:

- A perfect protection of all types of metals that are used in modern engines and their cooling systems.
- A neutral behavior towards seals, gaskets and hoses.
- A very good resistance against formation of foam.

### Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 210 L.

### Application

This coolant may be used all the year round in the cooling-systems of gasoline- and diesel engines.

Coolant is ready to use.

Do NOT add water.

Protection against freezing: down to -26°C.

### Photo



### Typical properties

Density 15°C	kg/l	1.06
pH (33 % in water)		8.2
Reserve alkalinity	ml	>8
Crystallization point°C		-26
Colour:		Blue

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)

TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.

URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)