



MULTI CK-4 SYNTHETIC L.S SAE 10W40 15W40

Synthetic Engine Oil

Beschrijving

Multi CK-4 Synthetic L.S SAE 10W40 15w40 is a synthetic diesel motor oil with 'low saps' technology for all diesel engines with the following properties:

- Extended lifetime of the engine.
- Prevent pollution of the engine.
- High resistance against oxydation.
- High viscosity index.

Kwaliteitsniveau

ACEA	E9-16	JASO	DH-2
API	CK-4	MB	228.31
API	CJ-4	MTU	Type 2.1

Beschikbaar in

Barrels of 30, 60 en 208 L.

Toepassing

Multi CK-4 Synthetic L.S SAE 10W40 15w40 is a diesel motor oil with 'low saps' technology for all diesel engines and particularly recommended for the following types:

Renault:RLD-4, Volvo:VDS-4.5 and Mack EO-S 4.5.

Also recommended for trucks which have to meet the challenging requirements of the latest CO2 emission for diesel engines in Europe.

Foto



Typische kenmerken

Density 15°C	0.860
Viscosity cst 40°C	92.5
Viscosity cst 100°C	13.7
Viscosity index	150
Pourpoint °C	-42
Flashpoint COC °C	226

Gemiddelde analyse zonder verbintenis

DENICOL
LUBRICANTS

DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)

TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.

URL <http://www.denicol.com> • EMAIL denicol@denicol.com