



MULTI SPECIAL C4 SAE 5W30

Synthetic Low Ash Oil

Description

Multi Special C4 is a full synthetic lubricant, specially developed to protect the after-treatment systems and is based on extremely high qualified base oils.

It offers:

- Excellent protection to gasoline and diesel engines in passenger cars, with or without turbo – with a DPF and a TWC (three way catalyst)
- Economy in fuel consumption, lowered CO2 emission
- Excellent engine cleanliness and durability

Quality level

ACEA C4-12
MB 229.51 – 226.51
RENAULT RN 0720

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

Multi Special C4 is specially developed to protect the after-treatment systems of gasoline and diesel engines in passenger cars, with or without turbo – with a DPF and a TWC (three-way catalyst)

Photo



Typical properties

Density 15°C	0.852
Viscosity cst 40°C	68
Viscosity cst 100°C	11.7
Viscosity index	169
Pourpoint °C	-38
Flashpoint COC °C	219

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com