



VACUUM OIL ISO VG 46 – 68 – 100 - 150

Solvent Refined Paraffinic Base Oil

Description

Vacuum Oil is an oil, blended from solvent refined paraffinic base oils with a very high oxidation stability, making this oil particularly suitable for vacuum pumps. It contains a minimal quantity of additives, which provide :

- Sufficient anti-wear protection
- Anti-rust and anticorrosion
- Good dispersant properties
- Natural high viscosity index
- No negative influence due to temperature fluctuations.

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

Particularly suitable for vacuum pumps working under heavy duty conditions.

Photo



Typical properties

| | VG 46 | VG 68 | VG 100 | VG 150 |
|---------------------|-------|-------|--------|--------|
| Density 15°C | 0.866 | 0.874 | 0.885 | 0.889 |
| Viscosity cst 40°C | 45.5 | 68.8 | 103 | 148 |
| Viscosity cst 100°C | 7.1 | 8.7 | 11.2 | 14.3 |
| Viscosity index | 115 | 98 | 95 | 95 |
| Pourpoint °C | -30 | -27 | -21 | -21 |
| Flashpoint COC °C | 217 | 224 | 235 | 245 |

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. ● Kromstraat 54 ● 2520 Ranst (Antwerp-Belgium)
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. ● FAX +32 (0)3.485.81.93.
 URL <http://www.denicol.com> ● EMAIL denicol@denicol.com