



WAY OIL ISO 32-68-100-150-220

Stick-Slip Extreme Pressure Lubricant

Description

Way Oil is a mineral oil, specially designed for the lubrication of slideways of metalworking machinery. By adding special additives shocks (stick-slip) will be avoided and it increases the adhesive and lubricating characteristics.

This oil is mainly preferred in slides of machinery, chains, reductions and lubrication of devices, in which situations splashing oil should be prevented.

Quality level

CINCINATTI ISO 32: P53
ISO 68: P47
ISO 220: P50

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

Specially designed for the lubrication of slideways of metalworking machinery.

Photo



Typical properties

	ISO 32	ISO 68	ISO 100	ISO 150	ISO 220
Density 15°C	0.872	0.884	0.891	0.895	0.899
Viscosity cst 40°C	32	69.2	100	156	210
Viscosity cst 100°C	5.4	9	12.4	15.1	17.9
Viscosity index	102	104	117	97	93
Pourpoint °C	-29	-37	-20	-35	-19
Flashpoint COC °C	201	211	213	222	242

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)

TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.

URL <http://www.denicol.com> • EMAIL denicol@denicol.com