



A1 COMPETITION

High Performance 2-Stroke Oil - Octane Stimulator

Description

A1 Competition is an extra high performance oil for two-stroke engines used in competition, motor-cross, karts, etc, where drivers demand the maximum from their machines under the most extreme conditions.

However, the oil is also perfectly suitable for use in standard two-stroke engines. It is formulated from mineral base oils and special synthetic additives which allow the product to maintain its lubricating properties under the most extreme conditions. This oil is non-premixed and not recommended for use in oil injection systems. Mixture ratio 2,5 % (1/40).

Quality level

API/CEC: TC

Available in

Carton of 24x1 L.
Barrels of 30, 60 and 208 L.

Application

For race, kart, endurance and cross.

Photo



Typical properties

| | |
|---------------------|-------|
| Density 15°C | 0.885 |
| Viscosity cst 40°C | 208 |
| Viscosity cst 100°C | 19.2 |
| Viscosity index | 110 |
| Pourpoint °C | -26 |
| Flashpoint COC °C | 192 |

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com