



# GEAR OIL HYPOID EP GL.5 SAE 80W90

Extreme Pressure High Performance Transmission & Gear Oil

## Description

Gear Oil Hypoid EP GL.5 SAE 80W90 is a lubricant, extremely suitable for use in heavy duty transmissions in rear axles, gear boxes and all transmissions where an API GL4 or GL5 oil is recommended.

This oil guarantees excellent friction properties, resulting in very smooth gear shifting without vibrations.

- Very high oxidation and thermic stability
- Fuel saving properties
- Safe for seals
- Longer maintenance intervals
- Excellent anti-wear protection

## Quality level

API: GL-5, GL-4  
 MIL: L-2105 C/D  
 ZF: TE-ML 05A, 16C, 19B, 07A, 12E, 16B, 17B  
 MAN: 342 M-1, M-2

## Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

Suitable for heavy duty transmissions in rear axles, gear boxes and all transmissions where an API GL4 or GL5 oil is recommended.

## Photo



## Typical properties

Density 15°C	0.896
Viscosity cst 40°C	147
Viscosity cst 100°C	14.7
Viscosity index	99
Pourpoint °C	-34
Flashpoint COC °C	211

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
 URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)