



# LONG DRIVE M.S.T. SAE 5W30 – 5W40

Hi-Tech Synthetic Long Life Motor Oil

## Description

Long Drive M.S.T. SAE 5W30 and 5W40 is a fuel economic, universal motor oil, developed according to the most recent technology for cars with exhaust gas treatment systems, to the extension of the lifetime of particulate filters and catalysts.

This DEXOS2-approved oil is highly recommended for the latest generation of GM/OPEL/CHEVROLET and VAUXHALL.

- Life Time of Particulate Filters
- Gasoline - Diesel - Turbo - LPG
- "Mid SAPS" Technology
- Fuel economy and lower CO2 emission
- Gasoline and diesel engines that meet the Euro 4 and Euro 5 standard

## Quality level

API	SN/CF
ACEA	A3, B4, C3/C2
MB	Approval 229.31/229.51
BMW	LL-04
GM	DEXOS 2-Approval
VW	502.00/505.00/505.01

## Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

Recommended for use in petrol and diesel engines in passenger cars and delivery vans with extended oil drain intervals, to the extension of the lifetime of particulate filters.

## Photo



## Typical properties

	SAE 5W30	SAE 5W40
Density 15°C	0.855	0.852
Viscosity cst 40°C	67.1	85
Viscosity cst 100°C	12.2	14.2
Viscosity index	182	175
Pourpoint °C	-36	-36
Flashpoint COC °C	234	214

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)

TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.

URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)