



## PRO SYN 4 SAE 5W40

Full Synthetic Multi-grade Engine Oil

### Description

Pro Syn 4 SAE 5W40 is a lubricant on full synthetic base, especially designed to answer to the highest VW-specifications (VW 505.1) for diesel engines. By using the latest technologies, this engine oil provides an excellent performance on the latest TDI-engines with pump injector units and a high protection of the exhaust catalyst.

### Quality level

API	SN/CF
ACEA	A3/B4-04/C3-08
VW	505.01, 502.00, 505.00
FORD	WSS-M2C 917-A
MB	229.31
BMW	LOGLIFE-04
RENAULT	RN 0700, RN 0710

### Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

### Application

PRO SYN 4 SAE 5W40 is especially developed for the lubrication of TDI-engines with pump injector units. This oil is also suitable for the most Euro-4 and Euro-5 engines of passenger cars.

### Photo



### Typical properties

	SAE 5W40
Density 15°C	851
Viscosity cst 40°C	84.7
Viscosity cst 100°C	13.9
Viscosity index	170
Pourpoint °C	-39
Flashpoint COC °C	235
Sulphated Ash	0.8

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)