



RACING 2 SYNTEX

Hi-Tech Synthetic 2-Stroke Oil - Premix & Injection Systems

Description

Racing 2 Syntex is a 2-stroke injector lubricant of superior quality containing synthetic base oils and an advanced additive system.
Provides optimum performances and keeps the engine clean.
Prevents scuffing and ring sticking.
Exceeds the world's leading manufacturers requirements for Hi-Tech 2-stroke motorcycle engines.
Smokeless.
For pre-mix and injection systems.
Mixture ratio 2.5 % (1/40).

Quality level

JASO: FD LOW SMOKE

Available in

Carton of 24x1 L.
Barrels of 30, 60 and 208 L.

Application

For high-speed 2-stroke engines.

Photo



Typical properties

Density 15°C	0.865
Viscosity cst 40°C	60
Viscosity cst 100°C	9.5
Viscosity index	145
Pourpoint °C	-36
Flashpoint COC °C	90

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. ● Kromstraat 54 ● 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. ● FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> ● EMAIL denicol@denicol.com