



UNIQUE SUPERGRADE SAE 15W40 – 15W50 – 20W50

Economy Multigrade Engine Oil

Description

Unique Supergrade is a multifunctional engine oil, especially manufactured of high quality refined base oils to which high standard additives were added to obtain the following characteristics:

- Very good anti-wear and anti-oxidation protection
- Strong detergency and dispersion power
- High protection against corrosion and foaming
- Excellent and stable viscosity index
- No negative effects on exhaust gas catalyst

Quality level

API	SG/CD
MIL	MIL-L-2014 B, MIL-L-46152 B

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

Highly recommended for the lubrication of all gasoline engines, diesel engines and LPG-engines of passenger cars and light trucks with or without turbo-charging.

Photo



Typical properties

	SAE 15W40	SAE 15W50	SAE 20W50
Density 15°C	0.883	0.883	0.890
Viscosity cst 40°C	110	135	158
Viscosity cst 100°C	14.0	17.5	18.0
Viscosity index	128	143	125
Pourpoint °C	-26	-26	-24
Flashpoint COC °C	220	230	240

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
 URL <http://www.denicol.com> • EMAIL denicol@denicol.com